

FD8DO

8 Digital Output Modbus Module

- 8 Digital Output
- DIN-rail mounting
- Relay outputs
- Modbus RTU



Connections and Measurements

It can be used as Remote I / O under PLC. It has 8 digital relay outputs.

- Digital Outputs (Relay contact)

Communicates with MODBUS RTU protocol via 1 RS-485 connection
2 RS-485 ports on the device for easy operation. The status of all ports
is indicated by communication signal and electric LED

Technical Specifications

General	: 32 Bit işlemci ARM Cortex
Supply Voltage	: 24VAC \pm %10 (50 - 60 Hz) veya 24VDC \pm %10
Power Consumption	: 10VA
I/O Ports	: 8 Port Digital Relay output
Communication Protocol	: MODBUS RTU (Slave)
Operating Temperature	: -20 °C to 70 °C
Operating Humidity	: %5 to %85
Storage Temperature	: -40 °C to 85 °C
Storage Humidity	: %5 to %95 (non-condensing)
Device Size	: 158 x 96.5 x 58.5 m
Package size	: 196 x 134 x 62 mm
Weight	: 300 gr
Mounting	: 35mm DIN Rail or Wal
Termination	: Screw Terminal Block

Modbus Register address :

Register type (COIL STATUS).Register addresses starting from 1 ito 8 coil status.
(For PLC type can start from 0.)


Modbus Address: FD8DO The Deep-Switches on the device are used to supply the Modbus address. Up to 255 addresses can be given. Each deep-switch indicates a number in binary number sequence.


- ❖ deep-switch 8 (ST128) = 128
- ❖ deep-switch 7 (ST64) = 64
- ❖ deep-switch 6 (ST32) = 32
- ❖ deep-switch 5 (ST16) = 16
- ❖ deep-switch 4 (ST8) = 8
- ❖ deep-switch 3 (ST4) = 4
- ❖ deep-switch 2 (ST2) = 2
- ❖ deep-switch 1 (ST1) = 1

Modbus Speed: The FD8DO Module communicates via the RS485 serial port in the Modbus RTU protocol.

- ❖ **BaudRate** : 9600
- ❖ **Databits** : 8
- ❖ **Parity** : None
- ❖ **StopBits** : 1

DEVICE DIMENSIONS :



<p>Turkey : UL Listed,Files (TS EN 55024, TS EN 55032,TS EN 61000-3-2,TS EN 61000-3-3 TS EN 61000-4-3) Energy Management Equipment Equipment : (FD-8DO Model Only)</p>	<p>Compliance</p> 
<p>Contact : Helenium Twins Residence Soğanlık Yeni Mah.Baltacı Mehmet Paşa Sk. No:1 B/Blok D/1 KARTAL – İSTANBUL Phone : +90 216 306 31 28 Mail : www.aidcontrols.com</p>	

The performance specifications are nominal and conform to acceptable industry standard. For application at conditions beyond these specifications, consult the AID Controls office. AID Controls shall not be liable for damages resulting from misapplication or misuse of its products.